


Multi-layer Power Inductor : MIPS2520D series (High current Type)



MIPS2520D series
(2.5 x 2.0 x 1.0mm max)

Features

- 2.5x2.0 mm and 1.0 mm in height (compact size): CAE and fine printing technology made this compact size possible
- Stable minimum DC resistance in the class
- High speed mounting: Using SMT mounter makes less than a second mounting possible
- Excellent mounting strength by SMD chip making
- Reduced noise over 2/3 of coil inductor by optimal design of CAD
- Completely lead-free product and support lead-free solder

Applications

- DC-DC converters and power modules used for the following equipments. Compact electrical instruments such as cellular phones, DSC, DVC, PDA, DVD and HDD.



Specifications

Product name	MIPS2520D 100	MIPS2520D 6R8	MIPS2520D 4R7	MIPS2520D 3R3	MIPS2520D 2R2	MIPS2520D 1R5	MIPS2520D 1R0	MIPS2520D 0R5
Inductance(μ H) at 1MHz	10 \pm 30%	6.8 \pm 30%	4.7 \pm 30%	3.6 \pm 30%	2.0 \pm 30%	1.6 \pm 30%	1.3 \pm 30%	0.6 \pm 30%
DC resistance(ohm)	0.28 \pm 30%	0.26 \pm 30%	0.28 \pm 30%	0.12 \pm 30%	0.11 \pm 30%	0.10 \pm 30%	0.09 \pm 30%	0.06 \pm 30%
Rated current(A)_typ.*1	0.7	0.8	0.7	1.0	1.1	1.2	1.2	1.4
Rated current(A)_typ.*2	0.2	0.3	0.6	0.4	0.9	1.2	1.4	3.2


Rated current_*1 : In case temperature rise to 40°C due to self-heating.

Operating temperature range: -40~85°C

Rated current_*2 : The saturation current : L=-30% down from initial L value.




Shapes and Dimensions



Standard package : Emboss taping (reel)

Recommended land pattern



(mm)